

ULTRAMAX™ MIMO B

Up to 7-in-1 High Performance External Antenna

ULTRAMAX MIMO B is a full outdoor antenna designed specifically to provide high performance connectivity for Fleet and Public Safety vehicles and assets connecting to almost any vehicular router or modem. This antenna is configurable and offers up to two high gain Cellular/LTE/MIMO antennas, which include support for LTE Band 14 for FirstNet, four high gain Wi-Fi antennas, and a GNSS antenna inside a single robust and compact housing. This antenna provides the ultimate in Wi-Fi support - with integrated 4x4 Wi-Fi antennas, providing support for full HD streaming video and other high bandwidth applications.

- Built-in ground plane (to accommodate installation on non-metal surfaces)
- 2 x Wideband LTE/cellular Elements (MIMO)
- 4 x 2.4 & 4.9-6 GHz Wi-Fi/WiMax Elements (MIMO)
- 1 x GNSS Element
- Seven or less embedded antenna technologies that operate over multiple bands in one housing
- Leading LTE performance while in coexistence with multiple other embedded antenna technologies
- Lower profile and smaller footprint than competing solutions
- High gain provides bigger cellular footprint
- Available in black or white
- US Patent 10109918



Optimal MIMO Performance for LTE



Compact and Robust UV Resistant Housing



Full Outdoor Installation Ready



Customizable Cables and Connectors to Connect to Any Modem



Flexible Mounting Options



GNSS



Low loss cable accessories



Fast custom turnaround time



Bolt Mount



Adhesive Mount

Standard Configurations

AP-CCWWWG-BQ-S222222-RP3456-BL-15	Cell/LTE x 2, Wi-Fi x 4, GNSS X 1, Threaded Bolt Mount, SMA on Cell/LTE & GNSS, RP-SMA on Wi-Fi, Black, 15ft coax
AP-CCWWWG-BA-S222222-RP345-BL-15	Cell/LTE x 2, Wi-Fi x 3, GNSS X 1, Adhesive Mount, SMA on Cell/LTE & GNSS, RP-SMA on Wi-Fi, Black, 15ft coax
AP-CCWWG-BQ-S22222-RP34-BL-15	Cell/LTE x 2, Wi-Fi x 2, GNSS X 1, Threaded Bolt Mount, SMA on Cell/LTE & GNSS, RP-SMA on Wi-Fi, Black, 15ft coax
AP-CCWG-BA-S2222-RP3-BL-15	Cell/LTE x 2, Wi-Fi x 1, GNSS X 1, Adhesive Mount, SMA on Cell/LTE & GNSS, RP-SMA on Wi-Fi, Black, 15ft coax
AP-CCW-BQ-S222-RP3-BL-15	Cell/LTE x 2, Wi-Fi x 1, Threaded Bolt Mount, SMA on Cell/LTE, RP-SMA on Wi-Fi, Black, 15ft coax
AP-CCG-BA-S222-BL-15	Cell/LTE x 2, GNSS X 1, Adhesive Mount, SMA on Cell/LTE & GNSS, Black, 15ft coax
AP-CC-BQ-S22-BL-15	Cell/LTE x 2, Threaded Bolt Mount, SMA on Cell/LTE, Black, 15ft coax
AP-WWWWG-BQ-S22222-RP1234-BL-15	Wi-Fi x 4, GNSS X 1, Threaded Bolt Mount, SMA on GNSS, Black, 15ft coax
AP-WWWG-BA-S2222-RP123-BL-15	Wi-Fi x 3, GNSS X 1, Adhesive Mount, SMA on GNSS, Black, 15ft coax
AP-WWG-BQ-S222-RP12-BL-15	Wi-Fi x 2, GNSS X 1, Threaded Bolt Mount, SMA on GNSS, Black, 15ft coax
AP-WW-BQ-S22-RP12-BL-15	Wi-Fi x 2, Threaded Bolt Mount, RP-SMA, Black, 15ft coax
AP-WWW-BA-S222-RP123-BL-15	Wi-Fi x 3, Adhesive Mount, RP-SMA, Black, 15ft coax
AP-WWWW-BA-S2222-RP1234-BL-15	Wi-Fi x 4, Adhesive Mount, RP-SMA, Black, 15ft coax

Also available in color white, customizable cable lengths up to 35 feet, and other connector variations.

Electrical Data

Frequency Range	Elements 1 & 2	698-960/1700-2700 MHz	
	Elements 3, 4, 5 & 6	2.4/4.9-6.0 GHz	
	Element 7	1550~1610 MHz	
Operational Bands	Elements 1 & 2	LTE/Cellular	
	Elements 3, 4, 5 & 6	Wi-Fi	
	Element 7	GPS L1/GALILEO E1/GLONASS G1/BeiDou B1/QZSS L1	
Peak Gain: Isotropic	Elements 1 & 2	698-960 MHz	4.9 dBi
		1710-2700 MHz	7 dBi
	Elements 3, 4, 5 & 6	2.4 GHz, 5.5 GHz	7 dBi, 5 dBi
		Element 7	30.50 dBi
Isolation	Elements 1 & 2	> 10 dB	
	Elements 3, 4, 5 & 6	> 30 dB	
Correlation Co-efficient	Elements 1 & 2	< 0.1	

Environmental Data

Hazardous Substances	RoHS Compliant
Temperature	-40°C to 65°C (-40°F to + 149°F) Operating and Storage conformance to IEC 60068
Humidity (Non-Condensing)	5% to 96% Operating and Storage conformance to IEC 60068
Water Ingress	IP67
Military Spec	MIL-STD 810 conformance to vibration

Mounting Data

Dimensions	Height	2.183" (55.5 mm)
	Width	7.074" (179.7 mm)
	Length	7.650" (194.3 mm)
Color	Black (BL) or White (WH)	

Cable Data

Cell/LTE & GNSS	Type	CFD195 Low Loss	Wi-Fi	CFD195 Low Loss
	Diameter	0.195" (4.953 mm)		0.195" (4.953 mm)
	Length	1 feet		1 feet
	Termination	SMA Male		RP-SMA Male

GNSS Data - Ceramic Patch Antenna Specification

Bandwidth	1561 – 1602 MHz
Gain@Zenith	2.5 dBi
Polarization	R.H.C.P.
Axial Ratio	3.0 dB Typ.

GNSS Data - LNA Specification

Noise Figure	1.2 dB
Gain	28 dBi
Voltage	3.3V~5.6V
Current	9.6±1mA@3.3V